

PORTABLE VISUALIZER V-850

Multi-function professional presenter
with VGA and a 3" LCD monitor



Specifications

Video	Camera element	1/4" Color interline-transfer CCD
	Effective pixel	1024H x 768V (800,000 pixels)
	Scanning frequency	625 Line, 2:1 Cross scanning
	Horizontal resolution	470 TV lines
	LCD monitor	3"
	Signal model	PAL color system
	Camera rotation	Up/down 135°
	Negative-positive switching	Yes
	White balance	Auto/preset (indoor/outdoor) (Auto white balance range: 2800°~ 8000°K)
	Signal-to-noise	>48dB (brightness > 1000 Lux)
	Min. illumination	Min. 1 Lux (F1.6 income adding model)/ 301RE
	Baselight compensation	Built-in (manual/automatic)
Input & Output	Video input	VGA x 1, S-Video x 2, Video x 2
	Video output	VGA x 2, S-Video x 1, Video x 1
	Audio input	Audio L/R x 2
	Audio output	Audio L/R x 1
	Mic output	66dB 600Ω
	Input selector	3 channels (video imager, A/V1, A/V2)
	Analog RGB input/output	Yes
Optics	Lens	F1.6 ~ 2.4, f = 3.9 ~ 63.0mm
	Zoom	32x powered zoom
	Focus	Powered/automatic
	Iris	Powered/automatic
Lighting	Sidelight	9W fluorescent lamp x 2 (folded up for storage)
	Backlight	16W fluorescent lamp
Power	Power Input	AC220V ~ 240V, 50 ~ 60Hz
Dimensions & Weight	Working stage dimension	250(W) x 330(L)mm
	Set-up dimension	550(W) x 455(D) x 570(H)mm
	Folded dimension	360(W) x 550(D) x 180(H)mm
	Weight	5kg
Others	Wireless remote control	Supplied
	Operation temperature	0°C ~ 45°C
	Environmental temperature	-20°C ~ 60°C

* All specifications or measurements are subject to change without prior notice